

# STRIKE Array 4C

## FEATURES

- Intense 4 pod color blinder/strobe rated IP65 for all-weather use
- Full range of color and excellent rendition of any color temperature of white
- Emulated "red shift" to mimic incandescent fixtures perfectly.
- Individual pan (or tilt depending on mount orientation) of each head to allow for directional adjustment of light output.
- Innovative interlocking system to connect multiple STRIKE Array family fixtures together.
- Multiple mounting locations and repositionable yoke with ¼ turn adaptors for creative and convenient rigging options
- Independent pod control and strobe functionality for high-impact effects on the fly



## SPECIFICATIONS

### OPTICAL

- Light Source: 268 LEDs (112 quad-color RGBA, 156 WW), 2.7W to 4.32 W, (871 mA), 50,000 hours life expectancy.
- Color Temperature (range): 2800 to 6500 K
- Color Temperature (at full): 5991 K
- CRI (@3200K): 94.6
- Beam Angle: 59.6°
- Field Angle: 102.2°
- Lumens: 53,481
- Illuminance: 1979 lux @ 5 m
- Selectable PWM: 600Hz, 1200Hz, 2000Hz, 4000Hz, 6000Hz, 25000Hz

### DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 30 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes

### CONSTRUCTION / PHYSICAL

- Dimensions: 19.17 x 16.70 x 6.45 in (487.02 x 424.21 x 163.84 mm)
- Weight: 34.4 lb (15.4 kg)
- Exterior Color: Black
- Housing Material: Magnesium alloy

### CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 5-pin Seetronic IP65 XLR or Seetronic IP65 etherCON
- Cable Length (power): 5 ft (1.5 m)

- Software Update: USB-C

## **CONTROL**

- Control Protocol: Art-Net, sACN, DMX ,RDM
- Modes/Personalities: 10 personalities (1, 3, 5, 7, 10, 12, 13, 16, 22 or HSV)

## **ELECTRICAL**

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 1180 W, 9.92 A @ 120 V, 60 Hz
- Power and Current: 1150 W, 5.60.20 A @ 208 V, 60 Hz
- Power and Current: 1140 W, 5.02 A @ 230 V, 50 Hz

## **CERTIFICATIONS / QUALIFICATIONS**

- CE, MET, FCC, ETL, cULus,
- IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE valve
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

## **WHAT'S INCLUDED**

- STRIKE Array 4C
- Seetronic Powerkon IP65
- Omega bracket with mounting hardware

## **OPTIONAL ACCESSORIES**

- STRIKE Array Flush Bracket
- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-08
- IP Rated Seetronic® Powerkon Extensions
- IP Rated DMX cables
- IP Rated EtherCon Cables
- UPLOAD 03 software uploader