

Intimidator Spot 260X

HIGHLIGHTS

- Compact moving head designed for mobile events
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- ¼-turn hanging bracket allows for quick removal when needed
- Project crisp gobos from nearly any distance with the motorized focus
- Manual zoom for short or long throw applications
- 3-facet prism splits the beam and covers a larger area
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Link up to 4 fixtures to create eye-catching, synchronized shows in Automated or Sound mode
- powerCON®-compatible power input/output connections saves setup time
- Fits best in the CHS-2XX VIP Gear Bag
- Available in black or white to fit different applications
- White housing not available in European Markets.



SPECIFICATIONS

- DMX Channels : 8 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/234°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/234°, 180°, 90° tilt
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 aluminum + 1 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable
- Light Source : 1 LED (cool white) 75 W, (3.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20Hz
- Power Linking : 7 units @ 120 V; 11 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
124 W, 1.8 A @ 120 V, 60 Hz
128 W, 1 A @ 230 V, 50 Hz
- Weight : 12.2 lb (5.6 kg)
- Size : 9.1 x 6.4 x 13.8 in (232 x 163 x 351 mm)
- Approvals : CE, UKCA, RoHS
- Gobo Size : 24 mm outside, 20 mm image, 1.1 mm max thickness
- Prism : 3-facet round, static
- Zoom angle (manual) : 12° to 17°
- Illuminance (12°) : 17,458 lux @ 2 m
- Illuminance (17°) : 12,848 lux @ 2 m
- Color Temperature : 15,000 K
- Bracket Mounting Hole : 13 mm
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- Fixture
- Power cord
- Hanging bracket
- Quick Reference Guide