

Intimidator Spot 475ZX

HIGHLIGHTS

- Compact moving head designed for large events
- Onboard USB-C port allows for quick software updates
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- Dual rotating prisms split the beam for great effects and cover a larger area
- Motorized zoom for short or long throw applications
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- powerCON®-compatible power input/output connections saves setup time



SPECIFICATIONS

- DMX Channels : 10 or 16
- DMX Connectors : 3 XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors : 7 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 aluminum + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (cool white) 250 W, (10 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Lumens : 10,710
- Power Linking : 3 units @ 120 V; 7 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
378 W, 3.4 A @ 120 V, 60 Hz
372 W, 1.9 A @ 230 V, 50 Hz
- Weight : 36.2 lb (16.5 kg)
- Size : 14.3 x 10 x 21 in (363 x 250 x 531 mm)
- Approvals : CE, UKCA, RoHS, MET
- Gobos : 8 + open, indexing, continuous scroll at variable speeds
- Gobo Size : 25.7 mm outside, 21 mm image, 1.3 mm max thickness
- Prism : 5-facet linear, bi-directional at variable speeds
- Prism : 6-facet round, bi-directional at variable speeds
- Zoom Angle (motorized) : 13° to 28°
- Illuminance (13°) : 90,979 lux @ 2 m
- Illuminance (28°) : 24,565 lux @ 2 m
- Illuminance (13°) : 14,557 lux @ 5 m
- Illuminance (28°) : 3,930 lux @ 5 m
- Color Temperature : 15,000 K
- Optional Controllers : RFC, RFC-XL

WHAT'S INCLUDED

- Fixture
- Power cord
- Hanging bracket
- Quick Reference Guide