

# 4BAR Hex ILS

## HIGHLIGHTS

- Complete wash lighting solution fitted with high-intensity, hex-color (RGBAW+UV) LEDs
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with 6-in-1 LED technology
- Update the unit's software from the built-in USB port
- Out of the box wireless control with included footswitch or optional IRC-6 controller
- Easily set up and tear down in minutes with the included tripod stand and carrying bags
- Achieve total room or stage coverage with 4 individually adjustable heads
- Increase mounting options by safely mounting to truss using built-in bolts



## SPECIFICATIONS

- DMX Channels : 6, 8, or 27
- DMX Connectors : 3-pin XLR
- Max Unobstructed Distance : (foot switch): 100 ft (30.5 m)
- Light Source : 42 LEDs (hex color RGBAW+UV) 5.1 W, (2 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 16°
- Field Angle : 25°
- Illuminance : 1570 lux @ 2 m (per pod)
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :  
97 W, 1.3 A @ 120 V, 60 Hz  
94 W, 0.7 A @ 230 V, 50 Hz
- Weight : 12.2 lb (5.5 kg)
- Size : 45.7 x 2 x 12 in (1186 x 50.8 x 305 mm)
- Approvals : CE, RoHS, UKCA
- Footswitch battery : 9 V
- Operating Frequency (D-Fi) : 2.412 to 2.484 GHz
- Operating Frequency (foot switch) : 433 MHz
- Stand Height : 7 ft 4 in (2.2 m)
- Fits Tripod Sizes : 1.5 in (36.80 mm)
- Bracket Mounting Hole : M10 (1.5 mm pitch)
- Weight (Controller) : 1.2 lb (0.6 kg)
- Size (Controller) : 16.5 x 5.2 x 1.5 in (419 x 132 x 38 mm)
- Optional Controllers : IRC-6, ILS Command

## WHAT'S INCLUDED

- 4BAR Hex ILS
- Power cord
- Carrying bag
- Tripod
- Tripod Carry bag
- Wireless Footswitch
- Quick Reference Guide