

COLORband Pix ILS

HIGHLIGHTS

- Full-size LED strip light functions as a pixel mapping effect, blinder, or wall washer
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Create amazing animations and video effects with individual LED control
- Convenient access to multiple pre-built programs with or without DMX
- Easily generate complex shows with ShowXpress Pixels
- Achieve flicker-free video operation with high-frequency LED dimming
- Ideal for quiet applications due to silent operation and no moving parts
- Easily transports in the optional CHS-60 VIP Gear Bag

SPECIFICATIONS

- DMX Channels : 3, 4, 6, 7, 8, 9, 12, 18, 36 or 41
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 12 LEDs (tri-color RGB) 3 W (1,000 mA), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 14°
- Field Angle : 27°
- Illuminance :
(2m): 4,142 lux @ 2 m
(5m): 663 lux @ 5 m
- Lumens : 1402
- Power Linking : 19 units @ 120 V; 35 units @ 230 V
- Power and Current :
49 W, 0.7 A @ 120 V, 60 Hz
48 W, 0.4 A @ 230 V, 50 Hz
- Weight : 7 lb (3.2 kg)
- Size : 38.9 x 2 x 6.2 in (987 x 49 x 157 mm)
- Approvals : CE, MET, UKCA, RoHS
- Cable Length : 5 ft (1.5 m)
- Bracket Mounting Hole : 13 mm
- Optional Controllers : RFC, RFC-XL, DFI-USB



WHAT'S INCLUDED

- Fixture
- Power cord
- Quick Reference Guide