

SlimBANK H18 ILS

HIGHLIGHTS

- Versatile hex-color LED wash light with brilliant eye candy effects
- ILS compatibility for use in the ILS ecosystem
- Generate complex looks easily with built-in, eye-catching auto programs with sectional control
- Adjustable barn doors help direct and focus the light
- Control options include IRC-6 remote, Master/Slave, DMX, or ILS
- Achieve smooth LED fading with built-in dimming curves
- Ideal for sound-sensitive environments due to the radiant cooling design and no fan
- Save time running extension cords by power linking multiple units.

SPECIFICATIONS

- DMX Channels : 6, 8, 12 or 22
- DMX Connectors : 3-pin XLR
- Light Source : 18 LEDs (hex-color RGBAW+UV) 6.2 W, (1.6 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 27°
- Field Angle : 43°
- Illuminance : 3,111 lux @ 2 m
- Lumens : 3,356
- Power Linking : 8 units @ 120 V; 14 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 68 W, 1 A @ 120 V, 60 Hz, 67 W, .5 A @ 230 V, 50 Hz
- Weight : 6 lb. (2.7 kg)
- Size : 8.2 x 14 x 2.2 in (208 x 355 x 55 mm)
- Approvals : CE, RoHS
- Optional Controllers : IRC-6, ILS Command
- Bracket Mounting Hole : 13 mm
- Beam Angle : 27°
- Field Angle : 43°
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)

WHAT'S INCLUDED

- SlimBANK H18 ILS
- Power cord
- Barn doors
- Quick Reference Guide

