

COLORstrip Pix ILS

HIGHLIGHTS

- Full-size LED strip light functions as a pixel mapping effect, uplight, or for great eye-candy effects
- ILS compatibility for use in the ILS ecosystem
- Create dazzling effects by linking multiple units together to make runway chases
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Create amazing animations and video effects with individual LED control
- Ideal for quiet applications due to silent operation and no moving parts
- Wireless, non-DMX operation is available with the optional IRC-6 remote
- Easily transports in the optional CHS-60 VIP Gear Bag

SPECIFICATIONS

- DMX Channels : 3, 8, 120, 122
- DMX Connectors : 3-pin XLR
- Light Source : 40 LEDs (tri-color) 2 W, (0.8A), 50,000 hours life expectancy.
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 14°
- Field Angle : 24°
- Illuminance : 4,967 lux @ 2 m
- Lumens : 1,491
- Power Linking : 7 units @ 120 V; 10 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
79 W, 1.2 A @ 120 V, 60 Hz
77 W, 0.8 A @ 230 V, 50 Hz
- Weight : 6.2 lb. (2.8 kg)
- Size : 38.9 x 2 x 6.2 in (987 x 49 x 157 mm)
- Approvals : CE, ROHS
- Cable Length : 5 ft (1.52 m)
- Bracket Mounting Hole : 13mm
- Optional Controllers : IRC6, ILS Command



WHAT'S INCLUDED

- COLORstrip Pix ILS
- Power cord
- Quick Reference Guide