Cumulus HP

HIGHLIGHTS

- Professional low-lying fog machine creates thick clouds that hug the floor
- Continuous operation produces fog on demand
- Ultrasonic agitator converts distilled water into a thin mist
- Fast heat up time allows for quick operation
- Rugged and light-weight case makes transportation a
- Control via built-in digital display, DMX or included wireless remote



- DMX Channels : 2 DMX Connectors : 3-pin XLR
- Heat-Up Time: 2 min Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz
- Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz
 Power and Current:
 1608 W, 13.4 A @ 120 V, 60 Hz
 1541 W, 6.7 A @ 230 V, 50 Hz
 Weight: 34.6 lb (15.7 kg)
 Size: 18.3 x 11.9 x 13.7 in (464 x 304 x 347 mm)
 Approvals: CE, UKCA, ROHS
 Tank Capacity: 2 gal (7.5 l)
 Output: 15,000 cfm
 Capacity (fon): 0.5 gal (2.1)

- Capacity (fog): 0.5 gal (2 l)
 Capacity (water): 2 gal (7.5 l)
 Fluid Consumption (fog): 11 ml/min
- Fluid Consumption (water): 87 ml/min

- Hose diameter: 4.8 in (123 mm)
 Hose length: 14 126 in (35 320 cm)
 Power and Current: 1608 W, 13.4 A @ 120 V, 60 Hz
 Compatible Fluids: LLG

WHAT'S INCLUDED

- Cumulus HP
- Hose, coupler and clamps
- Floor nozzle
- Wireless remote
- Power cord



