

SlimPAR Q12 ILS

HIGHLIGHTS

- Low-profile, high-output quad-color (RGBA) LED Par
- ILS compatibility for use in the ILS ecosystem
- D-Fi™ USB compatibility for wireless Master/Slave or DMX control
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with punchy amber LEDs
- Convenient access to RGBA color mixing and static colors with or without DMX
- Flicker-free operation suitable for on-camera use
- Increase standalone versatility with multiple user-configurable settings
- Save time running cables and extension cords by power linking multiple units
- Easily control static colors and automated programs with the optional IRC-6 remote
- Fits best in the CHS-30 VIP gear bag
- Compact design easily fits inside sticks of TRUSST®



SPECIFICATIONS

- DMX Channels : 4 or 9
- DMX Connectors : 3-pin XLR
- Light Source : 12 LEDs (quad-color RGBA) 6 W, (2.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 17 Hz
- Beam Angle : 17°
- Field Angle : 29°
- Illuminance : 2,684 lux @ 2 m
- Power Linking : 10 units @ 120 V; 18 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
55 W, 0.8 A @ 120 V, 60 Hz
54 W, 0.5 A @ 230 V, 50 Hz
- Weight : 3.6 lb (1.6 kg)
- Size : 9.7 x 3.6 x 11.5 in (247 x 92 x 293 mm)
- Approvals : CE, RoHS, UKCA
- Optional Controllers : IRC6, D-Fi USB

WHAT'S INCLUDED

- SlimPAR Q12 ILS
- Power cord
- Quick Reference Guide