

# GigBAR Move ILS

## HIGHLIGHTS

- 5-in-1 lighting system that includes moving heads, derbies, washes, a laser and strobe effect pre-mounted on a single bar
- ILS compatibility for use in the ILS ecosystem (ILS) is a complete lighting ecosystem technology that provides an advanced, coordinated light show across multiple fixture types
- Control any ILS-enabled fixture wirelessly with built-in D-Fi transceiver
- Use the included RF remote to trigger the built-in shows without needing line of sight
- Separate color and gobo wheels in moving heads allow for creative programming
- Totem Mode keeps the moving heads focused on the dance floor
- Easy navigation and access to all functions, directly from the full-color LCD display
- Safely mounts to truss or ceilings using the 3/8 in threaded inserts
- System includes a tripod, wireless footswitch, RF remote and FREE carry bags to ensure quick setup
- Built-in UV LEDs illuminate florescent objects and make them pop
- Individual control of each effect ensures your show looks the way you need it to
- Easy control via stand-alone, DMX, wireless RF remote or wireless footswitch



## SPECIFICATIONS

- DMX Channels : 3, 27 or 46
- DMX Connectors : 3- pin XLR
- Pan and Tilt : 540°/180°
- Colors : (moving head): 7 + white, continuous scroll at variable speeds
- Gobos : (moving head): 7 + open, continuous scroll at variable speeds
- Light Source :  
(pars): 3 LEDs (quad-color RGB+UV) 3.5 W (1 A), 50,000 hours life expectancy  
(strobe): 4 LEDs (white & UV) 5 W (1 A), 50,000 hours life expectancy  
(derby): 6 LEDs (2 red, 2 green, 2 blue) 1 W (1 A), 50,000 hours life expectancy  
(moving head): 1 LED (cool white) 10 W (2.3 A), 50,000 hours life expectancy  
(laser): 650nm/100 mW (red) laser diode, 532 nm/30 mW (green) laser diode
- Strobe Rate : 0 to 20 Hz
- Beam Angle : (moving head): 11°  
(pars): 19°  
(strobe): 8°
- Field Angle : (pars): 30°  
(strobe): 18°
- Coverage Angle : (derby): 131°  
(laser): 93°
- Fits Tripod Size : 1.5 in (37.4 mm)
- Illuminance :  
(pars): 1,205 lux @ 2 m (per par)  
(moving head): 1056 lux @ 2 m (per head)  
(strobe): 86 lux @ 2 m (per LED)
- Power Linking : 7 units @ 120 V; 12 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :  
81 W, 1.1 A @ 120 V, 60 Hz  
79 W, 0.6 A @ 230 V, 50 Hz
- Weight : 23.4 lb (10.7 kg)
- Size : 43 x 5.7 x 17.7 in (1100 x 144 x 449 mm)
- Approvals : CE, RoHS, UKCA, FDA, FCC
- Stand Height : 4.8 ft to 8.3 ft (1.5 to 2.5 m)
- Tripod leg width : 3.9 ft (1.2 m)
- Footswitch Operating Frequency : 433 MHz
- Foot Switch Max Unobstructed Distance : 100 ft (30.5 m)
- Footswitch battery : 9 V alkaline
- Included Controllers : RF remote, wireless footswitch

## WHAT'S INCLUDED

- GigBAR Move ILS

- Power cord
- Carrying bag
- Tripod
- Footswitch
- RF Remote
- Quick Reference Guide
- Key and interlock (EU)