

GigBAR 2

HIGHLIGHTS

- 4-in-1 light that includes a pair of LED derbies, LED pars, a laser, and strobe effect all mounted on one bar
- Added UV in pars and strobes for increased color mixing and effects
- Cover any room or stage with 4 individually adjustable and interchangeable heads
- Get in and get out quickly with the included tripod, wireless footswitch and FREE carry bags
- Ready for every application using the included mounting brackets to attach to truss
- 4 high-power, LED strobe lights create exciting chase and slow motion effects
- Adjustable red and green laser scatters hundreds of bright dots and beams in all the right directions.
- Phenomenal built in automated and sound-activated programs that include all 4 effects to make one complete show
- Easily control from the display, included IRC-6, wireless foot switch or DMX to take your gig to a higher level
- Master/slave multiple units under the control of a single IRC or wireless foot switch
- Save time running cables and extension cords by power linking multiple units
- Complies with FDA performance standards for laser products except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007.



SPECIFICATIONS

- DMX Channels : 3, 11 or 23
- DMX Connectors : 3-pin XLR
- Light Source : (pars): 6 LEDs (Quad-color RGB+UV) 3.5 W (1 A), 50,000 hours life expectancy
(strobe): 4 LEDs (white & UV) 5 W (1.5 A), 50,000 hours life expectancy
(Derby): 6 LEDs (2 red, 2 green, 2 blue) 5 W (1.6 A), 50,000 hours life expectancy
650nm/100 mW (red) laser diode, 532nm/30 mW (green) laser diode
- Strobe Rate : (strobe): 0 to 18 Hz
- Beam Angle : (pars): 13°
(strobe): 8°
- Field Angle : (pars): 24°
(strobe): 18°
- Coverage Angle : (laser): 93°
(Derby): 114°
- Fits Tripod Size : 37.4 mm
- Illuminance : (pars): 1,205 lux @ 2 m (per head)
(strobe): 86 lux @ 2 m (per zone)
- Power Linking : 8 units @ 120 V; 15 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 68 W, 1 A @ 120 V, 60 Hz
64 W, 0.5 A @ 230 V, 50 Hz
- Weight : 25.6 lb, (11.6 kg)
- Size : 1185 x 110 x 386.5 mm
- Approvals : CE, FDA, FCC
- Stand Height : 1.5 to 2.5 m
- Tripod leg width : 1.2 m
- Foot Switch Operating Frequency : 433 MHz
- Foot Switch Max Unobstructed Distance : 30.5 m

- Footswitch battery : 12 V A23

WHAT'S INCLUDED

- Power cord
- IRC-6
- Tripod
- Tripod Carry bag
- Wireless footswitch
- Warranty card
- User Manual