

# Swarm Wash FX ILS

## HIGHLIGHTS

- 4-in-1 LED light that combines an RGBAW rotating derby, RGB+UV wash, red/green laser, and a ring of white SMD strobes
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless Master/Slave, or DMX control
- Access built-in automated programs via IRC6 remote, Master/Slave or DMX
- Red and green laser beams project thousands of beams for maximum coverage
- Generate complex looks easily with built-in, eye-catching automatic and sound-activated programs
- Save time running extension cords by power linking multiple unit
- Fits best inside the CHS-40 VIP gear bag



## SPECIFICATIONS

- DMX Channels : 2 or 18
- DMX Connectors : 3-pin XLR
- Light Source : (Wash) 8 LEDs (quad-color RGB+UV) 1.5 W, (600 mA), 50,000 hours life expectancy  
(Strobe) 12 LEDs (white) 1 W, (300 mA), 50,000 hours life expectancy  
(Laser): 650 nm/100 mW (red) laser diode, 520 nm/30 mW (green) laser diode
- Strobe Rate : 0 to 20 Hz
- Power Linking : 11 units @ 120 V; 20 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 51 W, 0.7 A @ 120 V, 60 Hz  
50 W, 0.4 A @ 230 V, 50 Hz
- Weight : 9.5 lb (4.3 kg)
- Size : 13.1 x 13 x 9.4 in (335 x 332 x 241 mm)
- Approvals : CE, FDA, RoHS, UKCA
- Optional controllers : IRC-6
- Coverage Angle : (laser) 82°  
(swarm): 65°  
(strobe): 71°  
(wash): 46°
- : Classified per EN/IEC 60825-1: 2014
- : Complies with FDA performance standards for laser products except for deviations pursuant to Laser Notice No. 56, dated May 8, 2019

## WHAT'S INCLUDED

- Swarm Wash FX ILS
- Power cord
- User Manual