

# WELL Batten 14 x4



## FEATURES

- A fully realized kit of (4) battery-operated black IP65-rated batten style fixtures, with (28) RGB warm white LEDs in (14) sections of control and a beam angle of 16 degrees.
- 14 individual zones of control for pixel mapping effects
- Battery run time selections of 5, 8, 12, and 18 hours of operation at full output
- Built-in battery charger allows fixture to operate while charging
- Built-in IP65 5-pin DMX in/out allows for wired data
- Built-in Seetronic IP65 PowerKon input/output
- Control over RDM, CRMX, or RF
- Easy connection to WELL COM and WELL COM 2 boxes for app control
- USB-C port for convenient software updates
- Pressure equalizing M6 Gore valve
- Built-in safety cable attachment point
- Easy-to-read OLED display
- Built-in theft alarm (audio and visual notification)
- Built-in PWM Adjustment
- Included RF remote
- Included 4 pack charging case

## SPECIFICATIONS

### OPTICAL

- Light Source: 28 LEDs (RGBW) 10W, (516mA), 50,000 hours life expectancy.
- Color Temperature (range): 2600 to 10,000K
- Beam Angle: 16°
- Field Angle: 33.8°
- Cutoff Angle: 64.1°
- Lumens: 3854 lm (AC power)
- Illuminance: 1050 lux @ 5 m (AC power) Lumens:
- Lumens: 2210 lm (OFF battery setting)
- Illuminance: 601 lux @ 5 m (OFF battery setting)
- Lumens: 2319 lm (5-hour battery setting)
- Illuminance: 631 lux @ 5 m (5-hour battery setting)
- Lumens: 1437 lm (8-hour battery setting)
- Illuminance: 392 lux @ 5 m (8-hour battery setting)
- Lumens: 890 lm (12-hour battery setting)
- Illuminance: 243 lux @ 5 m (12-hour battery setting)
- Lumens: 548 lm (18-hour battery setting)
- Illuminance: 148 lux @ 5 m (18-hour battery setting)
- Selectable PWM: 1000 Hz, 2000 Hz, 3000Hz, 4000Hz, 6000Hz, 25kHz

### DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 30 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No

### CONSTRUCTION/PHYSICAL

- Dimensions: 39.4 x 7.9 x 6.4 in (1001 x 200 x 163 mm)
- Weight: 16.4 lb (7.4 kg)
- Exterior Color: Black
- Housing Material: Aluminum diecast

### CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic PowerKon IP65
- Power Input (fixture and charging case): Seetronic PowerKon IP65

- Power Output (fixture and charging case): Seetronic PowerKon IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)
- Software Connection: USB-C

#### CONTROL

- Control Protocol: DMX, RDM, CRMX, NFC, RF
- DMX Channels: 5,8,14,66,85
- Modes/Personalities: 6 personalities (5ch,8ch,14ch,66ch,85ch)
- Wireless WDMX “G” Compatibility: G4S
- Wireless Lumen Radio Compatibility: CRMX

#### ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

##### Single unit

- Power Linking: 17 units @ 120 V; 30 units @ 208 V; 32 units @ 230 V
- Power and Current: 80 W, 0.67 A @ 120 V, 60 Hz
- Power and Current: 79 W, 0.40 A @ 208 V, 60 Hz
- Power and Current: 79 W, 0.37 A @ 230 V, 50 Hz

##### 4 Pack case

- Power Linking: 5 units @ 120 V; 9 units @ 208 V; 10 units @ 230 V
- Power and Current: 219 W, 2.04 A @ 120 V, 60 Hz
- Power and Current: 222 W, 1.27 A @ 208 V, 60 Hz
- Power and Current: 222 W, 1.1 A @ 230 V, 50 Hz

#### CERTIFICATONS / QUALIFICATIONS

- CE, UKCA, FCC, ROHS
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

#### WHAT'S INCLUDED

- (4) Well Batten 14
- (1) 4 slot charging case
- (1) basic RF controller
- (4) Seetronic PowerKon IP65 power cords
- (8) Omega Brackets
- (1) QRG

#### OPTIONAL ACCESSORIES

- Clamps
- 15° filter pack
- 60°X10° filter pack
- PowerKon Extension cables
- 5 pin DMX Cables

