

WELL POD 2 X 6



FEATURES

- A fully realized kit of (6) battery operated black IP65-rated par style fixtures with (7) RGB warm white LEDs, and a beam angle of 12.8 degrees
- Battery run time selections of 5, 8, 12, and 18 hours of operation at full output
- Built-in battery charger allows fixture to operate while charging
- Built-in IP65 5-pin DMX in/out allows for wired data
- Built-in Seetronic IP65 PowerKon input/output
- Control over DMX, RDM, CRMX, or RF
- Easy connection to WELL CONNECT for app control
- USB-C port for convenient software updates
- Removable split yoke for both hanging and floor standing
- Pressure equalizing M6 Gore valve
- Built-in safety cable attachment point
- Easy-to-read OLED display
- Built-in theft alarm (audio and visual notification)
- Built-in PWM adjustment
- Included RF remote
- Included 6 pack charging case

SPECIFICATIONS

OPTICAL

- Light Source: 7 LEDs (RGBW) 7.5 W, (556 mA), 50,000 hours life expectancy
- Color Temperature (range): 2800 to 6500 K
- Beam Angle: 11.5°
- Field Angle: 21.6°
- Cutoff Angle: 36.9°
- Lumens: 1797 lm (AC power)
- Illuminance: lux 1089 @ 5 m (AC power)
- Lumens: 718 lm (OFF battery setting)
- Illuminance: 436 lux @ 5 m (OFF battery setting)
- Lumens: 834 lm (5-hour battery setting)
- Illuminance: 507 lux @ 5 m (5-hour battery setting)
- Lumens: 528 lm (8-hour battery setting)
- Illuminance: 319 lux @ 5 m (8-hour battery setting)
- Lumens: 335 lm (12-hour battery setting)
- Illuminance: 202 lux @ 5 m (12-hour battery setting)
- Lumens: 214 lm (18-hour battery setting)
- Illuminance: 129 lux @ 5 m (18-hour battery setting)
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4000 Hz, 6,000 Hz, 25000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 30 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No

CONSTRUCTION/PHYSICAL

- Dimensions: 8.11 x 5.31 x 8.76 in (206 x 138 x 222.5 mm)
- Dimensions (w/o bracket): 5.43 x 5.43 x 5.67 in (138 x 138 x 144 mm)
- Dimensions case: 32.7 x 19.3 x 15.4 in (832 x 492 x 390mm)
- Weight: 7.2 lb (3.3 kg)
- Exterior Color: Black
- Housing Material: Aluminum diecast

CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic PowerKon IP65
- Power Input (fixture and charging case): Seetronic PowerKon IP65
- Power Output (fixture and charging case): Seetronic PowerKon IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)
- Software Connection: USB-C

CONTROL

- Control Protocol: RDM, CRMX, NFC, RF
- DMX Channels: 5, 8, or 12
- Modes/Personalities: 3 personalities (5Ch, 8Ch, 12Ch)
- Wireless WDMX "G" Compatibility: G4S
- Wireless Lumen Radio Compatibility: CRMX

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Single unit

- Power Linking: 40 units @ 120 V; 64 units @ 208 V; 72 units @ 230 V
- Power and Current: 48 W, .4 A @ 120 V, 60 Hz
- Power and Current: 47.8 W, .23 A @ 208 V, 60 Hz
- Power and Current 48.3 W, .21 A @ 230 V, 50 Hz

6 Pack case

- Power Linking: 3 units @ 120 V; 6 units @ 208 V; 6 units @ 230 V
- Power and Current: 340 W, 3.33 A @ 120 V, 60 Hz
- Power and Current: 334 W, 1.89 A @ 208 V, 60 Hz
- Power and Current: 336 W, 1.72 A @ 230 V, 50 Hz
- 6 Pack case fuse: 250V, T5A

CERTIFICATONS / QUALIFICATIONS

- CE, UKCA, FCC, ROHS
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- (6) WELL POD 2
- (1) 6 slot charging case
- (6) detachable split yokes
- (1) RF controller
- (1) QRG

OPTIONAL ACCESSORIES

- Clamps
- 15° Lens pack
- 60°x10° Lens pack
- White metal cover
- IR remote
- PowerKon Extension cables
- 5 pin DMX Cables
- W-DMX Micro T-1 TRX G6

