

WELL POD 3 X 4



FEATURES

- A fully realized kit of (4) battery operated black IP65-rated par style fixtures, with (19) RGB warm white LEDs, and a beam angle of 12.7 degrees
- Battery run time selections of 5, 8, 12, and 18 hours of operation at full output
- Built-in battery charger allows fixture to operate while charging
- Built-in IP65 5-pin DMX in/out allows for wired data
- Built-in Seetronic IP65 PowerKon input/output
- Control over DMX, CRMX, RDM, or RF
- Easy connection to WELL COM and WELL COM 2 boxes for app control
- USB-C port for convenient software updates
- Removable split yoke for both hanging and floor standing
- Pressure-equalizing M6 Gore valve
- Built-in safety cable attachment point
- Easy-to-read OLED display
- Built-in theft alarm (audio and visual notification)
- Built-in PWM adjustment
- Included RF remote
- Included 4 pack charging case

SPECIFICATIONS

OPTICAL

- Light Source: 19 LEDs (RGBWW), 13.4W, (960mA) 50,000 hours life
- Color Temperature (range): 2800 to 6500 K
- Beam Angle: 12.7°
- Field Angle: 25.4°
- Cutoff Angle: 47.2°
- Lumens: 3557 lm (AC power)
- Illuminance: 1692 lux @ 5 m (AC power) Lumens:
- Lumens: 1994 lm (OFF battery setting)
- Illuminance: 946 lux @ 5 m (OFF battery setting)
- Lumens: 2177 lm (5-hour battery setting)
- Illuminance: 1033 lux @ 5 m (5-hour battery setting)
- Lumens: 1379 lm (8-hour battery setting)
- Illuminance: 655 lux @ 5 m (8-hour battery setting)
- Lumens: 845 lm (12-hour battery setting)
- Illuminance: 398 lux @ 5 m (12-hour battery setting)
- Lumens: 555 lm (18-hour battery setting)
- Illuminance: 261 lux @ 5 m (18-hour battery setting)
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 1 to 30 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No

CONSTRUCTION/PHYSICAL

- Dimensions: 9.76 x 7 x 10.86 in (248 x 178 x 276)
- Dimensions (w/o bracket): 9.76 x 7 x 7 in (248 x 178 x 178 mm)
- Dimensions case: 27 x 25.6 x 15 in (685 x 650 x 380 mm)
- Weight: 11.2 lbs (5.1 kg)
- Exterior Color: Black
- Housing Material: Aluminum diecast

CONNECTIONS

- Power Connection: Edison (local) plug to Seetronic PowerKon IP65
- Power Input (fixture and charging case): Seetronic PowerKon IP65
- Power Output (fixture and charging case): Seetronic PowerKon IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)
- Software Connection: USB-C

CONTROL

- Control Protocol: RDM, CRMX, NFC, RF
- DMX Channels: 4, 8, or 13
- Modes/Personalities: 3 personalities (4Ch, 8Ch, 13Ch)
- Wireless WDMX "G" Compatibility: G4S
- Wireless Lumen Radio Compatibility: CRMX

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Single unit

- Power Linking: 16 units @ 120 V; 27 units @ 208 V; 30 units @ 230 V
- Power and Current: 79 W, 0.74 A @ 120 V, 60 Hz
- Power and Current: 56 W, 0.43 A @ 208 V, 60 Hz
- Power and Current: 56 W, 0.39 A @ 230 V, 50 Hz

4 Pack case

- Power Linking: 2 units @ 120 V; 5 units @ 208 V; 5 units @ 230 V
- Power and Current: 306 W, 4.11 A @ 120 V, 60 Hz
- Power and Current: 306 W, 2.37 A @ 208 V, 60 Hz
- Power and Current: 305 W, 2.2 A @ 230 V, 50 Hz
- 4 Pack case fuse: T5A, 250V

CERTIFICATONS / QUALIFICATIONS

- CE, UKCA, FCC, ROHS
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): 14 °F to 113 °F (-10 °C to 45 °C)

WHAT'S INCLUDED

- (4) WELL POD 3
- (1) Charging case
- (4) Omega brackets
- (4) Detachable split yokes
- (1) RF controller
- Quick Reference Guide

OPTIONAL ACCESSORIES

- Clamps
- Lens pack (15 degree, 60x10 degree)
- Single charger
- White metal cover
- IR remote
- PowerKon Extension cables
- 5 pin DMX Cables

